TENDER DOCUMENT FOR PROCUREMENT OF COMPUTER HARDWARE, PERIPHERALS AND OTHER IT EQUIPMENTS



RMD Degree College of Sci. & Edn., Patia, BBSR-31 NAAC Accredited with B+ Grade

Dr Prasant Kumar Rout Principal

TERM & CONDITIONS

- RMD Degree College, Patia, BBSR-31 invites sealed bids from Agencies for Procurement of Computers and Accessories located at Patia, Bhubaneswar. The office must be strictly as per required specification and tenders terms & conditions for specified items in Annexure – 1.
- Bids are invited off-line through Registered post and by hand and bidding document can be downloaded from https://www.rmddc.ac.in on or before 11th April 2025 and submit same as per specified format by Before 11th April 2025 at 4:00 pm.
- 3. The intending firm should submit Rs.1000.00 tender fee (non-refundable), EMD Rs.24,000 (refundable) towards processing fees in shape of demand Draft in favour of "Raja M D Degree College of Science and Education, Patia" payable at Bhubaneswar along with tender documents, no exemption is allowed.
- 4. The Bidders should have office within Odisha State.
- 5. The Bidders must be obtained valid ISO 9001 / ISO 20000 Certificate.
- 6. The Bidders must be registered no of PAN/TAN and will submit IT Return copy of FY 2023-24.
- 7. The Bidder must have minimum annual turnover is greater than 20 Lakh in last financial two year (FY 22-23 & FY 2023-24) as certified by Chartered Accountant.
- 8. The Bidders must be registered under GST.
- 9. The bidder must have Bid specific Authorization Required from The OEM (Quoted Brand).Technical Compliance sheet on OEM Letter Head sign by Local Manager.
- 10. The bidders must be submitted minimum Three Years Experience.
- 11. The Bidder shall quote the item wise composite price for each item as per the price scheduled.
- 12. The intending bidder should submit as affidavit that his/her firm has not been black listed by any Govt Organization.
- 13. Tenders/Bidders are requested to regularly visit the website. Any modification in tender enquiry will be intimated by corrigendum through web site only and no separate Notification will be issued.
- 14. The quotations will be opened on 11th April 2025 at 4.00 pm at present of all bidder & committee members.
- 15. The Document two bid systems (Technical bid & financial bid in Separate cover). The prices quoted by the bidder shall remain fixed.

- 16. The intending bidder is not bound to accept the lowest quoted rate if the bidder not fulfill all requisites as considered necessary.
- 17. The payment will be released After successfully supply & installation.
- 18. Any legal dispute arising out of this is subject to Bhubaneswar jurisdiction only.
- 19. Authority reserves the right to accept or reject and bids or reject all tenders either in part or in full or to split the order bidding process without assigning and reason.

BID APPLICATION FORM

- 01. Name of the Bidder:
- 02. Address of the Bidder:
- 03. Cost of tender paper: (Tender Fee & EMD)

DD No	DD Date	Amount	Issuing Bank

Enclose:

The bidder should enclose the following records, duly self-Certified, in support of their bonafide: -

- 1. ISO Certificates Copy.
- 2. Income Tax Registration Certificate / PAN Copy.
- 3. GST Registration Certificate.
- 4. Minimum Two years' Experience (not less than 03(Three)) from Govt/Semi-Govt./Public Sector Organizations/Public Sector Banks regarding their similar contract between 2022-23 to 2023-24.
- 5. Quoted composite Price as per Annexure.
 - 6. The firm should submit a Affidavit copy to the effect that it has not been black listed by any Agency whatsoever till date.
- 7. Bid specific Authorization Required from The OEM (Quoted Brand).

Date :

Place:

Seal & Signature of the Bidder

ANNEXURE – I (Price Bid)

RMD Degree College, Patia

ITEM WISE- QUOTATION FOR PROCUREMENT OF COMPUTER & ACCESSORIES AT Raja MD Degree College of Sci., & Edn.,

SI. No.	Item Name	Make	Quantity	Unit Rate (Rs.)	Total	Taxes (%)	G. Total
1	Desktop		12				
2	UPS		12				
3	Printer		02				
4	LED TV- 65"		01				
5	Wireless Mic & Camera		01 each				
6	Internet Facility		00				
	TOTAL						

Total bid price (excluding taxes) in Rs. _____, in word Rupees

__only excluding taxes.

Note:

- a) In case of discrepancy between unit price and total price unit price shall prevail.
- b) We have quoted the above price after physical verification of the above assets in the Office premises & repair of any defective items is included in the above quoted price.

Date:	Seal & Signature of the quotationers
Place:	Name & Address of the firm

Desktop	Specification
Items	Specification
Cabinet Form Factor	Tower/Micro Tower (15.1 to 26 Litres)
Chipset Number	Intel H670/Intel® H770 or higher Chipset
Processor Make	Intel
Processor	x86 64-bit architecture
Processor Generation	13 Or higher
Processor Description	Intel Core i3 or higher
Processor Number	Intel Core i3 13100 or higher
Number of Cores and Threads per Processor	Max Turbo Frequency 4.5Ghz, Minimum 4 Cores and 8 Threads or higher
Operating System	Windows 11 Home Factory Preloaded
RAM Size (GB)	DDR-4 8GB 3200 (16 X1) or higher (2 DIIM Slots)
RAM Expandability up to (using spare DIMM Slots in GB)	64 GB or higher
Integrated Graphics	Intel UHD Graphics 770 or higher
Supported for discrete NVIDIA/AMD Graphics Card up to 6GB	Yes
Type of Drives used to populate the Internal Bays	NVMe SSD
Total HDD Capacity (GB)	NA
Total SSD Capacity (GB)	512GB NVMe SSD
Optical Drive	Optional
Drive Bays	Two 3.5" (2.5") HDD
	1 PCI Express 4.0 x16,
Slots for Upgradation	1 PCI Express 3.0 x1,
51013 101 0 2B 10221011	1 PCI (Full Height), 2 M.2 slots for WLAN & SSD
	LAN: Integrated 10/100/1000M
LAN	Front: 1 headphone/microphone combo; 3 Super Speed USB
Ports and Connectors	5Gbps signalling rate; 2 SuperSpeed USB 10 Gbps signalling rate; 1 USB Type-C, total 6nos USB in front for easy access Rear: 1 HDMI; 1 Serial Port; 1 line in; 1 line out; 1 power connector; 1 RJ-45; 1 DP; 2 USB 2.0
Firmware Trusted Platform Module	TPM 2.0
Hardware Security lock slot	Security lock slot
Power Supply	180-260Watt Internal power supply with minimum 90% efficiency
Power Supply	Bidder should submit OEM bid specific authorization & the same authorization may be verified by the respective OEM in required.
	OEM must have the ISO 9001,14001, ISO 20001, ISO 27001 Certificate
Certification	Microsoft Windows, Energy star 8.0 certified
	Bidder should submit BIS, BEE, EPEAT, UL, RoHS Certificate o
	products at the time of participation of the Bid.
Keyboard Mouse	USB Keyboard; USB Optical Mouse
Monitor	19.5" LED Display with CTO Certified and same must be belongs to the same OEM
Years of Warranty	3 Year Onsite Warranty

dispersion 10 Protection from Humidity & Dust UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity 11 Battery Saver Option UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years 12 No Load Shutdown UPS Should work on loads of 2-3 watts also 13 AC Surge Protection Full time, 160 joules 14 Automatic Re start of UPS In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time 4-6 hours 17 Operating Temperature 0°C to 40°C 18 Storage Temperature -15° C to 45° C 19 3 power outlets UP mit (normal mode) 20 Power Cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 13 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification Bits 25 Designed and Manufactured in India	SI. No.	Feature	General Specifications	
1 Discussion 2 Input Voltage 3 Input Voltage 3 Input Voltage 4 Brownout Transfer 1 145 VAC typical 5 Over-voltage Transfer 20 VAC typical 6 Voltage on Battery 7 Frequency – On Battery 8 Transfer Time 9 Air Ventilation 9 Air Ventilation 10 Protection from Humidity & Dust 10 Protection from Humidity & Dust 11 Battery Saver Option 12 No Load Shutdown 13 AC Surge Protection 14 Automatic Re start of UPS 15 Type (maintenance-free) 12 No Load Shutdown 14 Automatic Re start of UPS 15 Type (maintenance-free) 16 Typical recharge time 4 6 hours 17 Operating Temperature 18 Storage Temperature 19 3 power outlets 11 Battery Saver (to save on battery		UDS Capacity (total)	600VA/360W	
1 Input Frequency 45 - 65 Hz 4 Brownout Transfer 145 VAC typical 5 Over-voltage Transfer 290 VAC typical 6 Voltage on Battery 230 VAC typical (stepped approximated sine wave) 7 Frequency – On Battery 50Hz typical 8 Transfer Time @50 Hz : 6 ms typical, 10 ms max 9 Air Ventilation Should have Side and Back Honey bee Perforation for hear dispersion 10 Protection from Humidity & Dust UPS Should have conformal paint coating on PCB for Insulatio for Dust and Humidity 11 Battery Saver Option UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years 12 No Load Shutdown UPS Should work on loads of 2-3 watts also 13 AC Surge Protection Full time, 160 joules 14 Automatic Re start of UPS In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time 4.6 hours 17 Operating Temperature 0°C Cto 40°C 18 Storage Temperature 15°C Cto 45°C </td <td>_</td> <td>the second s</td> <td colspan="2"></td>	_	the second s		
3 Inport Transfer 145 VAC typical 4 Brownout Transfer 290 VAC typical 6 Voltage on Battery 230 VAC typical (stepped approximated sine wave) 7 Frequency – On Battery 230 VAC typical (stepped approximated sine wave) 8 Transfer Time Ø50 Hz : 6 ms typical, 10 ms max 9 Air Ventilation Should have Side and Back Honey bee Perforation for head dispersion 10 Protection from Humidity & Dust UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity 11 Battery Saver Option UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years 12 No Load Shutdown UPS Should work on loads of 2-3 watts also 13 AC Surge Protection Full time, 160 joules 14 Automatic Re start of UPS In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time -15 ^o C to 45 ^o C 17 Operating Temperature 0 ^o C to 45 ^o C 18 Storage Temperature -15 ^o C to 45 ^o C 19 <td< td=""><td></td><td></td><td colspan="2"></td></td<>				
5 Over-voltage Transfer 290 VAC typical 6 Voltage on Battery 230 VAC typical (stepped approximated sine wave) 7 Frequency – On Battery S0Hz typical 8 Transfer Time ØSO Hz : 6 ms typical, 10 ms max 9 Air Ventilation Should have Side and Back Honey bee Perforation for head dispersion 10 Protection from Humidity & Dust UPS Should have conformal paint coating on PCB for Insulatio for Dust and Humidity 11 Battery Saver Option UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years 12 No Load Shutdown UPS Should work on loads of 2-3 watts also 13 AC Surge Protection Full time, 160 joules 14 Automatic Re start of UPS In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time 4: 6 hours 17 Operating Temperature 0°C to 40°C 18 Storage Temperature 1.2 meters 19 3 power outlets With battery backup and surge protection 21 Runtime for Workstation PC (100	_			
5 Over congeneration 230 VAC typical (stepped approximated sine wave) 6 Voltage on Battery 230 VAC typical (stepped approximated sine wave) 7 frequency - On Battery 50Hz typical 8 Transfer Time @50 Hz : 6 ms typical, 10 ms max 9 Air Ventilation Should have Side and Back Honey bee Perforation for head dispersion 10 Protection from Humidity & Dust UPS Should have conformal paint coating on PCB for Insulatio for Dust and Humidity 11 Battery Saver Option UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years 12 No Load Shutdown UPS Should work on loads of 2-3 watts also 13 AC Surge Protection Full time, 160 joules 14 Automatic Re start of UPS In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time 4: 6 hours 17 Operating Temperature 0°C to 40°C 18 Storage Temperature -15° C to 45°C 19 3 power outlets 1.2 meters 21 Runtime for Single PC load	4	Brownout Transfer		
7 Frequency - On Battery SOHz typical 8 Transfer Time @50 Hz : 6 ms typical, 10 ms max 9 Air Ventilation Should have Side and Back Honey bee Perforation for head dispersion 10 Protection from Humidity & Dust UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity 11 Battery Saver Option UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years 12 No Load Shutdown UPS Should work on loads of 2-3 watts also 13 AC Surge Protection Full time, 160 joules 14 Automatic Re start of UPS in case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time 4 - 6 hours 17 Operating Temperature 0°C to 40°C 18 Storage Temperature -15°C to 45°C 19 3 power outlets With battery backup and surge protection 20 Power Cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W)	5	Over-voltage Transfer		
8 Transfer Time @50 Hz: 6 ms typical, 10 ms max 9 Air Ventilation Should have Side and Back Honey bee Perforation for heal dispersion 10 Protection from Humidity & Dust UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity 11 Battery Saver Option UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years 12 No Load Shutdown UPS Should work on loads of 2-3 watts also 13 AC Surge Protection Full time, 160 joules 14 Automatic Re start of UPS In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time 4- 6 hours 17 Operating Temperature -15° C to 45° C 18 Storage Temperature -15° C to 45° C 19 3 power cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24	6	Voltage on Battery	230 VAC typical (stepped approximated sine wave)	
9 Air Ventilation Should have Side and Back Honey bee Perforation for head dispersion 10 Protection from Humidity & Dust UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity 11 Battery Saver Option UPS Should have Battery Saver Option to increase the life of the Battery up to 5 years 12 No Load Shutdown UPS Should work on loads of 2-3 watts also 13 AC Surge Protection Full time, 160 joules 14 Automatic Re start of UPS In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time 4 · 6 hours 17 Operating Temperature -15° C to 40° C 18 Storage Temperature -15° C to 45° C 19 3 power outlets With battery backup and surge protection 21 Runtime for Single PC load (60W ± 15W) 13 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification Bits 25	7	Frequency – On Battery		
dispersion 10 Protection from Humidity & Dust UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity 11 Battery Saver Option UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years 12 No Load Shutdown UPS Should work on loads of 2-3 watts also 13 AC Surge Protection Full time, 160 joules 14 Automatic Re start of UPS In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time 4-6 hours 17 Operating Temperature 0°C to 40°C 18 Storage Temperature -15° C to 45° C 19 3 power outlets Uith battery backup and surge protection 20 Power Cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BiS 25 Designed and Ma	8	Transfer Time	@50 Hz : 6 ms typical, 10 ms max	
for Dust and Humidity 11 Battery Saver Option 12 No Load Shutdown 12 No Load Shutdown 13 AC Surge Protection 14 Automatic Re start of UPS 15 Type (maintenance-free) 16 Typical recharge time 17 Operating Temperature 18 Storage Temperature 19 3 power outlets 20 Power Cord 21 Runtime for Single PC load (60W ± 15W) 22 Runtime for Vorkstation PC (100W ±15W) 23 Battery backup on front panel 24 Certification 25 Designed and Manufactured in India 26 Warranty	9	Air Ventilation		
Battery upto 5 years 12 No Load Shutdown UPS Should work on loads of 2-3 watts also 13 AC Surge Protection Full time, 160 joules 14 Automatic Re start of UPS In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time 4-6 hours 17 Operating Temperature 0°C to 40°C 18 Storage Temperature -15° C to 45° C 19 3 power outlets With battery backup and surge protection 20 Power Cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty Zyeasrs	10	Protection from Humidity & Dust		
13 AC Surge Protection Full time, 160 joules 14 Automatic Re start of UPS In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time 4-6 hours 17 Operating Temperature 0°C to 40°C 18 Storage Temperature -15°C to 45°C 19 3 power outlets With battery backup and surge protection 20 Power Cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty Zyeasrs	11	Battery Saver Option	UPS Should have Battery Saver Option to increase the life of the	
14 Automatic Re start of UPS In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 12V, 7.2 Ah 16 Typical recharge time 4- 6 hours 17 Operating Temperature 0°C to 40°C 18 Storage Temperature -15°C to 45°C 19 3 power outlets With battery backup and surge protection 20 Power Cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty 2yeasrs	12	No Load Shutdown	UPS Should work on loads of 2-3 watts also	
switched off, when the grid power resumes the UPS Should Auto Start without human interference. 15 Type (maintenance-free) 16 Typical recharge time 16 Typical recharge time 17 Operating Temperature 18 Storage Temperature 19 3 power outlets 20 Power Cord 21 Runtime for Single PC load (60W ± 15W) 22 Runtime for Vorkstation PC (100W ±15W) 23 Battery Saver (to save on battery life) 24 Certification 25 Designed and Manufactured in India 26 Warranty	13	AC Surge Protection	Full time, 160 joules	
13 Typical recharge time 4- 6 hours 16 Typical recharge time 0°C to 40°C 17 Operating Temperature 0°C to 40°C 18 Storage Temperature -15°C to 45°C 19 3 power outlets With battery backup and surge protection 20 Power Cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty 2yeasrs	14	Automatic Re start of UPS	In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference.	
16 Typical recharge time 4- 6 hours 17 Operating Temperature 0°C to 40°C 18 Storage Temperature -15°C to 45°C 19 3 power outlets With battery backup and surge protection 20 Power Cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty 2yeasrs	15	Type (maintenance-free)	12V, 7.2 Ah	
18 Storage Temperature -15°C to 45°C 19 3 power outlets With battery backup and surge protection 20 Power Cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty 2yeasrs	16		4-6 hours	
19 3 power outlets With battery backup and surge protection 20 Power Cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty 2yeasrs	17	Operating Temperature	0° C to 40° C	
20 Power Cord 1.2 meters 21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty 2yeasrs	18	Storage Temperature	-15°C to 45°C	
21 Runtime for Single PC load (60W ± 15W) 27 min (normal mode) 22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty 2yeasrs	19	3 power outlets	With battery backup and surge protection	
22 Runtime for Workstation PC (100W ±15W) 13 min (normal mode) 23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty 2yeasrs	20	Power Cord	1.2 meters	
23 Battery Saver (to save on battery life) Thru toggle button on front panel 24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty 2yeasrs	21	Runtime for Single PC load (60W ± 15W)	27 min (normal mode)	
24 Certification BIS 25 Designed and Manufactured in India Yes 26 Warranty 2yeasrs	22	Runtime for Workstation PC (100W ±15W)	13 min (normal mode)	
25 Designed and Manufactured in India Yes Yes Yes Yes	23	Battery Saver (to save on battery life)	Thru toggle button on front panel	
26 Warranty 2yeasrs	24			
	25	Designed and Manufactured in India		
	26	Warranty	2yeasrs	

	Generic
Description of Stores	Multifunction Machine Printer with Minimum 1 Year On Site Warranty, including Cartridge and Power Cord/Adapter
Core Function	Print, Scan and Copy
Print Technology	Laser
Cartridge Technology	Composite Cartridge
Type of Printing	Monochrome (Black)
RAM Size (MB)	256
Storage Capacity (in GB)	0
Features	Fax
Operating System Compatibility	Windows 10 and Above,Linux,Mac OS,Windows Server
	Printing
Print Paper Size	A4 and Legal
Minimum Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Monochrome (Black) (in PPM)	26 to 30
Minimum Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Colour (in PPM)	Not Applicable
Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size- Mono (in PPM)	Not Applicable
Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size- Color (in PPM)	Not Applicable
Auto Duplexing Printing/Coping (2-sided Feature)	Yes
	Scanning
Maximum Scan Area (Platen/Flatbed Size)	A4 and Legal
A4 Scan Speed -Colour (Image Per Minute) @ 300 x 300 dpi	11 to 20
Scan To Functions	Email
A4 Scan Speed - Mono (Image Per Minute) @ 300 x 300 dpi	11 to 20
	COPYING
Reduction and Enlargement Feature	Yes

	PAPER HANDLING	
Original Document Feeder Type (For Scanning and Copying)	Automatic Document Feeders (ADF)	
Feeder Capacity (Number of Sheets) (For Scanning and Copying)	31 to 40	
Number of Main Paper Tray	1 -	
Total Paper Tray Combined Capacity (Number) at 75 GSM	101 to 200	
Bypass Tray Facility	No	
If Yes, Bypass Tray Capacity	0	
Connectivity		
Connectivity	USB Port,Ethernet Port,Wi-Fi	
Accessories Provided	USB Cable	
	Performance	
Minimum Yield of the Cartridge/Ink/Toner supplied with Machine as per IS/ISO/IEC: 19752/2017 for Black (Number of Prints)	700 -	
Minimum Yield of the Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints)	0	
Minimum Duty Cycle (Number of Prints/Month)	10,001 to 20,000	
	POWER	
Power Supply	Single Phase AC 220 - 240 V, 50 - 60 Hz-	
Maximum Power Consumption (in Watt)	1300	
Invironmental		
Minimum Operating Temperature (Degree C)	10	
Maximum Operating Temperature (Degree C)	30	

Minimum Operating Humidity (%RH)	20	
Maximum Operating Humidity (%RH)	80	
	Dimension	
Standard Machine Weight with Single Tray (in Kg)	11	
	Certification	
BIS CRS Compliance	Yes as per IS 13252 (Part 1)	
Maximum Number of Prints covered under Product warranty (Whichever is earlier)	30000	
EPR Registration in respect of the manufacturer/authorised importer as per E waste rules as amended up to date	Yes	
Agreed to Provide a copy of EPR Registration Certificate to the Buyer on Demand	Yes	

	Screen Size	65
	Brightness (cd/m²)	350Nits or better
	Contrast Ratio	1200:1
	Dynamic Contrast Ratio	400,000:1
General Features	Response Time (ms)	8.0
	Display resolution (H x V, pixels)	3840 x 2160
A STATE OF A STATE	HDR (High Dynamic Range) compatibility	Yes (HDR10, HLG)
	Aspect Ratio	16:9
	Portrait/Tilt Compatibility	Yes
	Dimming type	Frame Dimming
	Display Device	LCD
	Panel Type	IPS
	Backlight type	Direct LED
	Color gamut (NTSC)	69%
Display features		16/7
	Operation time	1%
	Haze (%)	178 (89/89) degree
	Viewing Angle (Right/Left)	178 (89/89) degree
	Viewing Angle (Up/Down)	4096 x 2160p (24, 50, 60 Hz),
	HDMI Signal	3840 x 2160p (24, 25, 30, 50, 60 Hz), 1080p (30, 50, 60 Hz), 1080/24p, 1080i (50, 60 Hz), 720p (30, 50, 60 Hz), 720/24p, 576p, 576i 480p,480i
	Speaker Position	Down Firing
Audio Specs	Audio Power Output	10W + 10W
	Pro settings	Yes (Simple Pro settings menu
Professional	HDMI auto wake-up	Yes
features	Operating System	Android TV
	On-board Storage (GB)	16GB
	RAM	3GB
	Wi-Fi Certified	Yes
Network Specs	Wireless LAN	Integrated
	USB playback codecs	MPEG1:MPEG1/MPEG2 PS:MPEG2/MPEG2 WEBM:AV1/AC4/ogg/AAC
Convenience	On Screen Clock	Yes
features	Sleep Timer	Yes
	On/Off Timer	Yes
-	Chromecast built-in	Yes
	Apple AirPlay	Yes
	IP Control	Yes
Control Specs	RS-232C Control	Yes
	HDMI-CEC	Yes
Marchen Colonia I and	HDCP	HDCP2.3 (for HDMI1/2/3)
	Composite Video Input (s)	1 (Side, Mini jack)

	HDMI inputs total	3 (3Side)
Inputs and outputs	Analog Audio Input (s) (Total)	1 (Side Analog Conversion)
	Digital Audio Output (s)	1 (Side)
	USB ports	2 (Side)
	Ethernet inputs	1 (Side)
Design features	VESA [®] Hole Pitch (W x H)	300 x 300 mm
	Rated Power Consumption	226W
Environment Specs	Power Consumption (in Standby)	0.5 W
chanonment specs	Dynamic Backlight Control	Yes
	Power Saving Mode / Back Light Off Mode	Yes
	Dimension of TV without Stand (W x H x D)	1462 x 842 x 71 mm
Measurements	Dimension of TV with Stand (W x H x D)	1462 x 912 x 338 mm
	Dimension of Package Carton (W x H x D)	1588 x 965 x 184 mm
	Weight of TV without Stand	20.4 kg
Weight	Weight of TV with Stand	21.3 kg
The second second	Weight of Package Carton (Gross)	28 kg